

Occhio


Coro moon zero v phase-cut datasheet

LED recessed downlight with fireball light source (non-tiltable). zero v downlight version for flush mounting in hollow ceilings with revision. The downlight is mounted with a separate mounting sleeve. Version with remote power supply unit, connection to 230 V AC mains voltage. Dimmable via phase-cut dimmer. The color temperature can be configured to 2700 K, 3000 K or 4000 K when ordering.

The innovative LED fireball technology creates a special lighting effect - direct light in forward direction and atmospheric illumination by the fireballs indirect light. The fireball as a light source has a light cone of 30°.







incl. power supply unit (removable)
L 165 × W 50 × H 23.6 (cable length 200)

technical data Coro moon zero v phase-cut


properties	material	aluminium, glass, painted, plastic
	weight	0.6 kg
surface	holding ring	white, black
Occhio LED	average life time	> 50.000 hrs
	energy efficiency class	This product contains a light source of energy efficiency class F (2700 K, 3000 K) or E (4000 K)
	power	LED 7 W (incl. Occhio power supply unit approx. 9 W, standby < 0.5 W)
	color rendering index	CRI Ra 92
	color temperature (color consistency)	2700K / 3000K / 4000 K (2-step)
electricity	dimming	via phase cut dimmer*
	connection	230 V AC
	permitted operating conditions	ambient temperature 10 – 30°C, for indoor use only


*** dimmer not included in the scope of delivery, for a list of compatible dimmers, see www.occhio.com/dim_en**

IP 20

Occhio

Coro moon zero v phase-cut lighting effects





moon
direct, glare-free light,
beam angle approx. 30°

optics:	Occhio fireball	
power:	high color	7 W
luminous flux:	2700 K	560 lm
	3000 K	600 lm
	4000 K	680 lm