Occhio


Sento sospeso pro pure datasheet

LED suspended luminaire with double sided light output, luminous power 2 ×18 W. Lighting effect changeable via optional inserts.

trimless-version with height adjustment
LED suspended luminaire freely height adjustable incl. plaster plate for flush mounting on hollow ceiling, connection to constant current source (driver). Extern dimmable (depending on the power supply unit).

trimless-version with fixed length
LED suspended luminaire with fixed height adjustment incl. plaster plate for flush mounting on hollow ceiling, connection to constant current source (driver). Extern dimmable (depending on the power supply unit).





* with Occhio converter

dimensions in mm

technical data Sento sospeso pro pure

properties	material	aluminium, steel chrome-plated, painted or anodised, plastic, glass, optical plastic	
	height adjustment (variable)	500 – 2000 mm (variable)	
	height setting (fix)	max. 3500 mm (can be adjusted during fitting)	
	weight	variable: 2.4 kg / fix: 1.9 kg	
surface	head	shiny chrome, dark chrome, matt chrome, glossy white, matt white, matt black, matt gold, rose gold, bronze, phantom, dark phantom	
	base	matt white	
Occhio LED	average life time	> 50.000 hrs	
	energy efficiency class (luminous efficiency)	G (74 lm / W)	
	power	LED 2 × 18 W max. 2 × 500 mA (> 36 V DC) / LED 2 × 13 W * max. 2 × 350 mA (> 36 V DC)	
	color rendering index	perfect color; CRI Ra 97	high flux; CRI Ra 85
	color temperature	2700, 3000 K	3000, 3500, 4000 K
electricity	dimming	with trailing edge phase cut dimmer, push button, DALI or 1–10 V (depends on driver)	
	power supply unit	remote, driven by constant current source max. 2 × 500 mA / 36 V DC	
	permitted operating conditions	ambient temperature 10–30°C, for indoor use only	

* version shiny chrome, dark chrome, rose gold, bronze, phantom, black phantom


IP 20

Sento sospeso pro pure
overview inserts

	Sento D	Sento E
lens		
diffuser glass		
soft edge glass (optional)		
satinised glass (optional)		
double-sided head		
satinised glass (optional)		
soft edge glass (optional)		
lens		
		

Sento sospeso pro pure
lighting effects






Sento D
directed light in both directions beam angle approx. 80°

inserts:	lens		
	lens		
luminous flux:	perfect color	2 × 18 W	2460 lm
	high flux	2 × 18 W	3380 lm
	perfect color	2 × 13 W	1690 lm
	high flux	2 × 13 W	2460 lm





Sento E
diffuse up light directed down light beam angle approx. 80°

inserts:	satinised glass		
	lens		
luminous flux:	perfect color	2 × 18 W	2300 lm
	high flux	2 × 18 W	3160 lm
	perfect color	2 × 13 W	1580 lm
	high flux	2 × 13 W	2300 lm